



topLine TA 9340

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Exhaust air system
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left
- Anthracite or chrome steel finish



topLine TC 9350

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Condensation system
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left
- Anthracite or chrome steel finish



topLine TW 9360

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Condensation system with heat pump
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left
- Anthracite or chrome steel finish

Company or brand name	Schulthess	Schulthess	Schulthess
Type of appliance	Exhaust air dryer	Condensation dryer with heat-exchanger air	Condensation dryer with heat pump
Type or sales description	topLine TA 9340	topLine TC 9350	topLine TW 9360
Product number	9340.2U	9350.2U	9360.2U
Load capacity	max. kg 8	8	8
Structural design			
Stand-alone unit with work surface	•	•	•
Standard unit for washing and drying tower	•	•	•
Door hinge ³⁾	r/l/w	r/l/w	r/l/w
Dimensions⁴⁾			
Height	cm 90	90	90
Width	cm 63	63	63
Depth including distance from wall	cm 83	84	84
Height for built-in installation	cm 90,5	90,5	90,5
Depth with door open	cm 144	146	146
Height (adjustable)	cm 2	2	2
Drying control			
By time selection ⁵⁾	•	•	•
Automatic by electronic moisture detection ⁶⁾	•	•	•
System and Equipment			
Drying technology	Air extraction system	Air condensation system	Condensation system with heat pump
Programme time display	•	•	•
Automatic door opening	•	•	•
Loading opening	cm front, Ø 36 / 31 / 180°	front, Ø 36 / 31 / 180°	front, Ø 36 / 31 / 180°
LED drum lighting	•	•	•
Connecting cable	m 1,5	1,5	1,5
Outlet hose	m –	2 / Ø 22 mm	2 / Ø 22 mm
Condensate drainage in container / Drainage direct	–	•	•
Exhaust air duct	Ø 100 mm, 90°-angle adapter	–	–
Maximum drain height	m –	1	1
Exhaust hose Ø 100 mm	m 2	–	–
Power supply – Electrical connection⁷⁾			
Voltage	V 400 V 3N~ / 400 V 2N~ / 230 V 1N~	400 V 3N~ / 400 V 2N~ / 230 V 1N~	400 V 2N~
Connected values	kW 5,9 / 4,4 / 2,2	5,1 / 3,7 / 2,3	3,4
Fuse protection	AT 10 / 10 / 10	10 / 10 / 10	10
Safety and service			
Conforms to the European Machinery Directive	2006/42/EC	2006/42/EC	2006/42/EC
Country of origin	Switzerland	Switzerland	Switzerland
Guarantee ⁸⁾	1 year	1 year	1 year
Service by	Schulthess Maschinen AG		
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH		

Explanations:

– Available or yes • Not available or no

3) Door hinge: l = left, r = right, w = can be changed

Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

4) The stated dimensions are minimum dimensions for the niche where the machine is built in. Further dimensions can be found in the dimension sheets.

5) Set the degree of drying according to the laundry items, as shown in the operating instructions.

6) Degree of drying is maintained automatically.

7) Information on switchover options can be found in the installation instructions, where required.

8) Outside Switzerland: 1 year

Note: State of the table details as 03.2021, subject to further developments.